

# FACTORY-MANUFACTURED SINGLE PLY MEMBRANE GUTTERS

#### WHAT ARE SPRA COMPONENT QUALITY STANDARDS?

SPRA Component Quality Standards set a benchmark of performance for products used in single ply membrane systems. They are a vital aid to specification and define the minimum technical standard for membership of the Association. All SPRA CQS are available by download from <a href="https://www.spra.co.uk">www.spra.co.uk</a>

#### PRODUCT DESCRIPTION

Galvanised steel substrate with an adhered polymeric membrane.

### **TYPICAL APPLICATIONS**

Uninsulated and insulated gutters in new construction and refurbishment.

REQUIREMENTS				
Product characteristic	Test Method	Machine-laminated	Manually laminated	
Membrane thickness (min)  CLASS A  CLASS B	ECCA-T1	1.2mm 0.6mm	1.2mm Not recommended	
Membrane adhesion	BS3900/E2	100% adhesion flat cross hatch + Erickson	100% adhesion flat cross hatch + Erickson	
Corrosion resistance – salt spray	ECCA-T8	1000 hrs	1000 hrs	
Corrosion resistance – humidity	BS3900/F2	1000 hrs	1000 hrs	
Scratch resistance	EN 13523-12			
Resistance to salt spray	EN 13523-8			
Maximum continuous operating temperature		80°C	80°C	
Minimum forming temperature		16°C	16°C	
Formation of joints		Hot air welded	Hot air welded	
Guarantee CLASS A CLASS B	Min 10 years – Max 25 years* Min 10 years - Max 15 years*			

<sup>\*</sup>In accordance with manufacturers terms and conditions

REQUIREMENTS FOR ON SITE TESTING AND INSTALLATION		
Membrane joint thickness	1.2mm (min)	
Compatible internal & external corner units and rainwater outlets available	YES	
Gutter and membrane manufacturer installation training required	YES	
Installation and maintenance guide	YES	
DECICAL COVETEN REQUIREMENTS		

## **DESIGN / SYSTEM REQUIREMENTS**

Gutter capacity to be designed to BSEN12056:3 – 2000 Roof drainage layout and calculation.

Gutter to be designed to withstand all anticipated loads in accordance with appropriate standards in regard to structural loading, wind loading, and non-fragility.

Manufacturer factory production control: ISO9001 accredited.

Manufacturer environmental management: ISO14001 accredited (or working towards).

Membrane to be supplied by SPRA member manufacturer.

## SPRA MEMBERS WHICH SUPPLY THIS PRODUCT

IKO Polymeric (www.ikogroup.co.uk) Tel: 01257 488000 Kingspan Limited (www.kingspanpanels.com) Tel: 01352 716100